

support rod adjacent the upper end of the open front side of said cabinet,

c) at least one towel support rod extending between and supported by said frame members adjacent the upper end of the open front side of said cabinet for hanging a towel vertically downward from said rod toward the bottom of said  
10 cabinet, and

d) means on the cabinet for mounting said support frame for movement of said at least one towel support rod through said open front side of the cabinet between a position retracted within the cabinet and a position extended forwardly of and adjacent the upper end of said open front end of the cabinet.

Add the following claims:

---

5. The towel warmer and dryer cabinet of claim 1 wherein the cabinet includes back and top members extending between said spaced side walls, a lavatory bowl supported by said top member, and drain means extending from the lavatory bowl downwardly through the cabinet adjacent said back member.

6. The towel warmer and dryer cabinet of claim 1 including a front panel supported pivotally on the upper end of the towel rod support frame for movement of said front panel between a retracted position substantially closing the open front side of said cabinet in the retracted position of said towel rod support  
5 frame and an extended position hanging downwardly and forwardly of said open

**Serial No. 10/016,047**  
**Group Art Unit: 3637**

**front side of said cabinet in the extended position of said towel rod support frame.**

**7. The towel warmer and dryer cabinet of claim 3 including a front panel supported pivotally on the upper end of the towel rod support frame for movement of said front panel between a retracted position substantially closing the open front side of said cabinet in the retracted position of said towel rod support frame and an extended position hanging downwardly and forwardly of said open front side of said cabinet in the extended position of said towel rod support frame.**

5

**8. The towel warmer and dryer cabinet of claim 1 wherein the cabinet bottom is open and a source of heated air current is mounted in the cabinet adjacent to and registering with said open bottom.**